

Dispersion Penalty for 1.3- μm Lightwave Systems with Multimode Semiconductor Lasers

GOVIND P. AGRAWAL, SENIOR MEMBER, IEEE, P. J. ANTHONY, MEMBER, IEEE,
AND T. M. SHEN, MEMBER, IEEE

Abstract—The effect of fiber dispersion on the performance of lightwave systems is analyzed for the case where multimode semiconductor lasers operating near the zero-dispersion wavelength of the single-mode fiber are used as sources. Both the intersymbol interference and the mode-partition noise are considered in the discussion of dispersion-induced power penalties. The theory is in good agreement with an experiment in which the bit error rate is measured for four lasers at various bit rates. The tolerable limits on the deviation of the laser wavelength from the zero-dispersion wavelength are obtained for a 1.3- μm system operating at 1.7 Gbit/s. Monte Carlo simulations are used to predict the effect of mode-partition noise on the performance of such high-speed lightwave communication systems.

I. INTRODUCTION

IT is well known [1], [2] that the group-velocity dispersion in single-mode fibers limits the performance of optical communication systems. Since the group-velocity dispersion vanishes at a specific wavelength λ_D , referred to as the zero-dispersion wavelength (ZDWL), the dispersive effects can be minimized by operating the lightwave system in the ZDWL vicinity. However, as an exact match between the laser wavelength λ_0 and the ZDWL λ_D is practically not feasible, the system performance depends on the wavelength deviation $\Delta\lambda = |\lambda_0 - \lambda_D|$. Since the dispersion penalty would generally vary from one fiber link to another depending on the values of the fiber and laser parameters, the goal of the system designer is to set the tolerance limits on both λ_0 and λ_D so that the distribution of dispersion penalties is below some predetermined level. The tolerance limits, however, depend on other laser and system parameters such as the bit rate B , the fiber length L , and the spectral width σ of the multimode semiconductor laser.

Since an unnecessarily tight specification on the laser wavelength is detrimental to laser yield, it is prudent to choose the wavelength window $\lambda_0 \pm \Delta\lambda$ as wide as possible within the system requirements. One objective of this paper is to consider the dependence of the dispersion-induced power penalty [3]–[6] on various parameters such as B , L , σ , and $\Delta\lambda$, and determine the tolerable $\Delta\lambda$ for a specific fiber link. The other objective is to determine the distribution of power penalties for the whole system through Monte Carlo simulations by including the al-

lowed link-to-link variations in the system parameters. Such simulations can then be used to predict the median and worst-case penalties. The results are applied to a specific 1.3- μm lightwave system operating at 1.7 Gbit/s to determine the tolerable wavelength deviation $\Delta\lambda$.

II. DISPERSION-INDUCED POWER PENALTY

There are two basic mechanisms through which the dispersion can induce power penalties for transmission systems making use of single-mode fibers.

1) The broadening of an optical pulse leads to intersymbol interference. Qualitatively speaking, the power loss occurring within the bit period B^{-1} has to be compensated by increasing the launched power in order to maintain the required signal-to-noise ratio (SNR) at the receiver.

2) Mode-partition noise in multimode semiconductor lasers (due to power redistribution among laser modes with the total power relatively constant) coupled with the fiber dispersion reduces the SNR at the receiver. This mechanism under some conditions can degrade the SNR so much that the system cannot achieve a specified bit error rate even by increasing the launched power (i.e., a bit-error-rate floor is observed).

A. Intersymbol Interference

It is generally difficult to estimate the amount of power penalty arising from the pulse broadening since it depends on details of the laser transmitter and the receiver. To develop a qualitative understanding, assume that the laser transmits a Gaussian pulse whose spectrum is also Gaussian, i.e.,

$$P(\lambda, t) = \frac{P_0}{\sigma\sqrt{2\pi}} \exp\left[-\frac{(\lambda - \lambda_0)^2}{2\sigma^2}\right] \exp\left[-\frac{t^2}{2T_0^2}\right] \quad (1)$$

where σ is the spectral half-width, T_0 is the temporal half width, and P_0 is the peak power. It can be shown [7] that the pulse remains Gaussian after propagation inside the fiber and the transmitted power (integrated over all wavelengths) at the receiver is given by

$$P_{\text{rec}}(t) = P_0 \left(\frac{T_0}{T}\right) \exp\left[-\frac{t^2}{2T^2}\right] \quad (2)$$

Manuscript received September 29, 1987; revised November 25, 1987. The authors are with AT&T Bell Laboratories, Murray Hill, NJ 07974. IEEE Log Number 8719287.

where

$$T = T_0 [1 + (DL\sigma/T_0)^2]^{1/2} \quad (3)$$

D is the dispersion (in ps/km-nm), and L is the fiber length. To relate T_0 to the bit rate B , we use the relation $T_0\sqrt{2\pi} = B^{-1}$ obtained by equating the Gaussian-pulse area to that of a square pulse of duration B^{-1} . The broadening factor of the pulse is then given by

$$T/T_0 = [1 + 2\pi(BDL\sigma)^2]^{1/2}. \quad (4)$$

A simple estimate of the dispersion penalty α_{ISI} due to intersymbol interference can be obtained by comparing the received power with and without dispersion at the decision point (assumed to be located at the pulse center). We then obtain (in decibels)

$$\alpha_{\text{ISI}} = 10 \log (T/T_0) = 5 \log [1 + 2\pi(BDL\sigma)^2]. \quad (5)$$

Since in all cases of practical interest $BDL\sigma \ll 1$, (5) can be approximated by

$$\alpha_{\text{ISI}} \approx 14(BDL\sigma)^2. \quad (6)$$

The preceding estimate of α_{ISI} is based on an oversimplified model. A more accurate calculation of the intersymbol-interference effects should take into account receiver details, in particular those related to the equalizer, and requires numerical simulations [8], [9]. In the following discussion, we use (5) to estimate the power penalty α_{ISI} . As a rough criterion, note from (6) that

$$|BDL\sigma| < 1/4 \quad (7)$$

in order to keep α_{ISI} at a level near or below 1 dB.

B. Mode-Partition Noise

Ogawa has studied in detail the power penalty due to mode-partition noise (MPN) using a simple model [3], [6]. We briefly discuss this model. It is assumed that the total power carried by each pulse is constant while the power in each mode fluctuates, i.e.,

$$\sum_{i=1}^N A_i = 1 \quad (8)$$

where $A_i(t)$ is a random variable denoting the instantaneous power in the i th longitudinal mode, N is the total number of longitudinal modes, and the total power has been normalized to unity. The measured time-averaged power spectrum $p(\lambda_i)$ shows the average value of the mode power at the mode-wavelength λ_i :

$$\begin{aligned} \bar{A}_i &= p(\lambda_i) \\ &= \int \cdots \int A_i p(A_1, A_2, \cdots, A_N) \\ &\quad \cdot dA_1 dA_2 \cdots dA_N \end{aligned} \quad (9)$$

where $p(A_1, A_2, \cdots, A_N)$ is the joint probability distribution function.

When the optical pulse is transmitted through the dispersive fiber, each mode is delayed by a different amount

because of group-velocity dispersion. If $f(\lambda_i, t)$ denotes the received waveform for i th mode, the total received signal is

$$r(t) = \sum_{i=1}^N f(\lambda_i, t) A_i. \quad (10)$$

The MPN leads to an additional noise at the receiver with the variance (evaluated at the decision time slot $t = t_0$).

$$\sigma_{\text{mpn}}^2 = \overline{r^2(t_0)} - [\overline{r(t_0)}]^2. \quad (11)$$

This noise is added to the receiver noise so that the effective SNR Q is determined by

$$\frac{1}{Q^2} = \left(\frac{\sigma_r}{S}\right)^2 + \left(\frac{\sigma_{\text{mpn}}}{1}\right)^2 \quad (12)$$

where σ_r is the total receiver noise and S is the received signal.

The MPN-induced power penalty is related to the increase in the received power that is necessary to maintain a constant SNR. Since in the absence of MPN, $S_0 = Q\sigma_r$ is the required power, the power penalty (in decibels) is given by

$$\alpha_{\text{mpn}} = 10 \log \left(\frac{S}{S_0}\right) = 5 \log \left(\frac{1}{1 - Q^2\sigma_{\text{mpn}}^2}\right). \quad (13)$$

The value of Q is determined by the maximum acceptable bit error rate (BER) using [6]

$$\text{BER} = \frac{1}{Q\sqrt{2\pi}} \exp(-Q^2/2). \quad (14)$$

$Q \approx 6.7$ if 10^{-11} is chosen as the maximum bit error rate. Equation (13) shows that the power penalty becomes infinite for

$$\sigma_{\text{mpn}} \geq Q^{-1} \approx 0.15$$

implying that a bit error rate of 10^{-11} cannot be achieved in that case (an error-rate floor above 10^{-9}). It is this feature of MPN that makes it of critical importance in the design of lightwave transmission systems.

C. Evaluation of σ_{mpn}

The evaluation of σ_{mpn} using (11) requires the knowledge of the joint probability distribution function $p(A_1, A_2, \cdots, A_N)$ which is generally unknown. Ogawa has introduced the concept of the mode partition coefficient k defined by [6]

$$k^2 = 1 - \alpha = \frac{\overline{A_i^2} - (\overline{A_i})^2}{A_i - (\overline{A_i})^2} \quad (\text{for any } i) \quad (15)$$

where it is assumed that $\overline{A_i A_j} = \alpha \overline{A_i} \overline{A_j}$ for all modes ($i \neq j$). The assumption that all modes have the same cross-correlation with respect to each other is the most critical assumption of this model and may not always hold for semiconductor lasers. Its use however allows the evaluation of σ_{mpn} without the knowledge of $p(A_1, A_2, \cdots, A_N)$.

Using (10), (11), and (15), one find that

$$\sigma_{\text{mpn}} = k \left[\sum_{i=1}^N f_i^2 \bar{A}_i - \left(\sum_{i=1}^N f_i \bar{A}_i \right)^2 \right]^{1/2} \quad (16)$$

where $f_i = f(\lambda_i, t_0)$. We assume that the received signal waveform after equalization at the receiver is of the form

$$f_i = f(\lambda_i, t_0) = \cos [\pi B(t_0 + \Delta \tau_i)] \quad (17)$$

where

$$\Delta \tau_i = LD(\lambda_i - \lambda_0) \quad (18)$$

is the relative delay of the i th mode with respect to the central mode at λ_0 during propagation for a fiber of length L and dispersion D . The decision circuit samples the received signal at times $t_0 = N/B$, where N is an integer, and therefore $f_i = \pm \cos(\pi B \Delta \tau_i)$ in (17).

The numerical value of σ_{mpn} depends on the steady-state spectrum \bar{A}_i which we assume to be Gaussian:

$$\bar{A}_i = p(\lambda_i) = \frac{1}{\sigma \sqrt{2\pi}} \exp \left[-\frac{(\lambda_i - \lambda_0)^2}{2\sigma^2} \right]. \quad (19)$$

The calculation is considerably simplified if we assume that the discrete sum in (16) can be replaced by an integral. The final result is

$$\sigma_{\text{mpn}} = \frac{k}{\sqrt{2}} [1 - \exp(-\beta^2)] \quad (20)$$

where

$$\beta = \pi BDL\sigma \quad (21)$$

is a dimensionless parameter. Our result (20) is a slight generalization of the Ogawa's result [3], [6] since we did not assume $\pi B \Delta \tau_i \ll 1$ in (17). In the limit $\beta \ll 1$

$$\sigma_{\text{mpn}} = k\beta^2/\sqrt{2} \quad (22)$$

and we recover the Ogawa's result. The calculation of σ_{mpn} can be generalized to include the effect of non-Gaussian spectrum by using the discrete sum in (16). We calculate our results for the MPN-induced power penalty using (13) and (20).

The expression (20) for the MPN noise shows that σ_{mpn} is directly proportional to the mode-partition coefficient k defined by (15). The numerical value of k is relatively uncertain and may depend on a large number of parameters such as the bit rate (through the pulse duration), the modulation depth (through the bias level), and the spectral width σ . Experimental measurements suggest a value of $k = 0.5$, and this value has been widely used [6]. It should however be stressed that the experimental data have been obtained for relatively wide pulses (>1 ns) and depend to some extent on the method of measurement.

III. RESULTS FOR 1.7-GBIT SYSTEM

In this section we present the results for a 1.3- μm light-wave transmission system operating at a bit rate of 1.7 Gbit/s. The dispersion parameter D is obtained assuming

that in the ZDWL vicinity D varies linearly with the wavelength deviation, i.e.,

$$D = S(\lambda_0 - \lambda_D) \quad (23)$$

where the slope $S = \partial D/\partial \lambda$ is evaluated at the ZDWL λ_D . The numerical values of the average slope and its standard deviation are obtained from measurements [10] on a large number of fiber segments (sample size of 6538) varying in length from 2–7 km. Table I shows the average values and the range of variations in the values of the parameters which control the dispersion penalty. In particular, the fiber length L is assumed to be uniformly distributed over the range 36–46 km. The other parameters S , λ_D , λ_0 , and σ are assumed to have a Gaussian distribution whose standard deviation is shown in Table I (under the range column). These parameter values are typical of realistic lightwave systems. To quantify the system performance, we consider both the median and the worst-case penalties. The median penalty is calculated by using the average values in Table I. The worst-case penalty is calculated by taking $L = 46$ km (the maximum fiber length), $S = 0.102$ ps/km/nm², and $\sigma = 2.5$ nm. The values of S and σ correspond to 2 standard deviations above the average value of the corresponding Gaussian distribution. For this choice the probability of a larger penalty than that calculated here is $< 10^{-3}$.

Consider first the dispersion penalty α_{ISI} due to intersymbol interference. Using the average parameter values from Table I in (5), we find that $\alpha_{\text{ISI}} \leq 0.5$ dB as long as $|\lambda_0 - \lambda_D| < 16$ nm. If we use (5) for the worst-case values of $L = 46$ km, $S = 0.102$ ps/km/nm², and $\sigma = 2.5$ nm, we find that for $\alpha_{\text{ISI}} \leq 0.5$ dB the wavelength window narrows down to

$$|\lambda_0 - \lambda_D| < 10 \text{ nm}. \quad (24)$$

This result shows that the intersymbol interference does not cause significant power penalty for wavelength deviations as large as 10 nm.

We next consider the dispersion penalty due to MPN. The average power penalty α_{mpn} for a bit error rate of 10^{-11} as a function of λ_0 is shown in Fig. 1 using the average parameter values given in Table I and (13), (20) and (21). Since the value of the mode-partition coefficient k is relatively uncertain, curves for $k = 0.5$ and $k = 1$ are shown. The power penalty increases rapidly with an increase in the wavelength deviation $|\lambda_0 - \lambda_D|$ and eventually becomes infinite (an error-rate floor at a level higher than a 10^{-11} bit error rate).

The wavelength window $|\lambda_0 - \lambda_D|$ to achieve α_{mpn} below a preselected level can be obtained as follows. If we use (22) and (23), we obtain

$$|\lambda_0 - \lambda_D| = \left(\frac{\sqrt{2}\sigma_{\text{mpn}}}{k} \right)^{1/2} \frac{1}{\pi BSL\sigma} \quad (25)$$

where from (13) σ_{mpn} is related to α_{mpn} by

$$\sigma_{\text{mpn}} = \frac{1}{6.7} (1 - 10^{-\alpha_{\text{mpn}}/5})^{1/2} \quad (26)$$




Fig. 1. Variation of the average power penalty α_{mpn} for a bit error rate of 10^{-11} with the lasing wavelength for the 1.3- μm system with parameter values given in Table I. The two curves show the strong dependence of α_{mpn} on the mode-partition coefficient k . The curves are symmetric around the zero-dispersion wavelength of 1308 nm.

TABLE I
NUMERICAL VALUES OF THE PARAMETERS FOR A 1.3- μm LIGHTWAVE SYSTEM OPERATING AT 1.7 GBIT/S

Parameter	Symbol	Average	Range
Fiber length	L	41 km	± 5 km
Dispersion slope	S	0.09 ps/km/nm ²	$\pm .006$ ps/km/nm ²
Zero-dispersion wavelength	λ_D	1308 nm	± 3 nm
Laser wavelength	λ_0	1308 nm	± 5 nm
Spectral width	σ	2.0 nm	± 0.25 nm

and we took $Q = 6.7$ corresponding to a bit error rate of 10^{-11} .

To provide the worst-case estimates of α_{mpn} for comparison with the median α_{mpn} , Fig. 2 shows $|\lambda_0 - \lambda_D|$ as a function of α_{mpn} using $L = 46$ km, $S = 0.102$ ps/km/nm², and $\sigma = 2.5$ nm. We note that in order to keep the dispersion penalty (for $k = 1$) below 0.5 dB:

$$|\lambda_0 - \lambda_D| < 5 \text{ nm.} \quad (27)$$

We can also calculate the wavelength window for the average penalty to be below 0.5 dB and find that (Fig. 1, $k = 1$)

$$|\lambda_0 - \lambda_D| < 8 \text{ nm.} \quad (28)$$

These ranges of wavelength deviation should be compared with (24). It is evident that the MPN is the limiting factor rather than the intersymbol interference and sets the final limit on the wavelength deviation $|\lambda_0 - \lambda_D|$ that can be tolerated, given these parameters.

IV. EXPERIMENTAL RESULTS

Since the dispersion penalties in Figs. 1 and 2 depend critically on the relatively unknown value of the model parameter k , system experiments were done using four lasers of varying wavelengths. As the dispersive effects




Fig. 2. Variation of the wavelength deviation $|\lambda_0 - \lambda_D|$ with the worst-case power penalty α_{mpn} for two values of the mode-partition coefficient k . The tolerable bit error rate is assumed to be 10^{-11} .

depend on the product $BDL\sigma$ [see (20) and (21)], the power penalty curves can be obtained by varying any one of the four parameters. We have found it convenient to vary the bit rate B . Fig. 3 shows the measured power penalty for a bit error rate of 10^{-10} as a function of the bit rate for the four lasers. Calculated curves show the theoretical fit to the experimental data. The laser wavelength λ_0 and the spectral width σ were obtained using the longitudinal-mode spectrum for each laser measured under the operating conditions. The measured fiber parameters were $L = 28.1$ km, $\lambda_D = 1306$ nm, and $S = 0.09276$ ps/km/nm². To obtain the fit shown in Fig. 3, it was necessary (1) to set $k = 1$ and (2) to choose the ZDWL 4.5 nm shorter than the measured value. The fitted value of λ_D is within the experimental uncertainty. The power penalty α_{mpn} predicted using $k = 0.5$ is significantly smaller than the measured values, and therefore $k = 1$ was used in the Monte Carlo simulations discussed in the next section.

It should be stressed that actual lasers are not expected to have $k = 1$ since it implies that at any time the laser output is concentrated in one mode only. The experimental measurements shown in Fig. 3 indicate that (20) underestimates the extent of MPN. The reason behind this underestimation can be traced back to the Gaussian form (19) for the mode spectrum. Although the Gaussian-spectrum assumption is often used and provides a reasonable fit for the central part of the experimental spectra, its use ignores the contribution of the spectral modes in the wings. If we use the discrete sum (16) in place of (20) and include the modes up to 30 dB down from the dominant mode, the experimental results can be fitted with a lower value of the mode-partition coefficient $k \approx 0.7$. Our recent work shows that the experimental spectra can be fitted by assuming a super-Lorentzian profile [11]. The use of this form has also resulted in $k \approx 0.7$. In our Monte Carlo simulations we have nonetheless used $k = 1$ in order to provide the worst-case estimates of the power penalty that are independent of the actual value of k .




Fig. 3. Measured system penalties at several bit rates for four lasers of different wavelengths and a fiber length of 28 km. Solid curves show the theoretical fit based on the mode-partition-noise model with λ_D as the fitting parameter. The theoretical curves for the data points denoted by circles and squares nearly coincide on the scale shown.

V. MONTE CARLO SIMULATIONS

Equations (27) and (28) show that the median and the worst-case estimates of the wavelength window are different and neither of them may be suitable for the system design. Clearly the worst case has a very low occurrence probability since several parameters have to take their worst values simultaneously. The resulting power penalty for the whole system can thus be estimated only in a statistical sense. For this purpose, we have performed Monte Carlo simulations to obtain the distribution of MPN-induced power penalties for a 1.7-Gbit/s system resulting from link-to-link variations in the laser and fiber parameters. In these simulations the laser and fiber parameters are chosen randomly assuming a mean and a standard deviation for a Gaussian distribution, and the range for a uniform distribution.

Table I shows the values of the five parameters varied randomly for the purpose of Monte Carlo simulations. The fiber length L is taken to be uniformly distributed over the range 36–46 km. Based on extensive measurements [10] on a large number of fiber segments, the ZDWL λ_D is assumed to obey a Gaussian distribution with mean 1308 nm and a standard deviation of 3 nm. The dispersion slope near the ZDWL is also found to satisfy a Gaussian distribution with parameters given in Table I. The dispersion parameter D is obtained by using (23). Both the laser wavelength λ_0 and the spectra width σ were found to vary as a Gaussian distribution for our laser population. We have however assumed that the distribution of λ_0 is a truncated Gaussian in the range 1308 ± 5 nm. This would be the case in practice if lasers are selected to have their wavelengths in that range.

The Monte Carlo simulations were performed for a sample size of 1000. The power penalty for each sample point was calculated by using (13) and (20). The results provide us with the distribution of power penalties. The distribution is nearly log-normal. The median penalty is

found to be negligible (≈ 0.02 dB). However, the variation is quite large, with each change of one standard deviation producing an order of magnitude change in penalty. Still, the power penalty is below 0.5 dB in 92 percent of the cases. The transmitters for which the dispersion penalty exceeds the system-allocated margin can be identified through the BER measurements using a fiber with nearly worst-case parameters. Our simulation results show that a wavelength window of 5 nm centered at the ZDWL ($\lambda_0 = \lambda_D \pm 5$ nm) can be used for 1.7 Gbit/s with only a few percent yield drop in transmitters.

VI. CONCLUSIONS

We have analyzed the effect of intersymbol interference and mode-partition noise on the performance of high-speed lightwave system operating near the zero-dispersion wavelength of single-mode fibers. It is found that the mode-partition noise is the limiting mechanism and sets the ultimate limit on the tolerable range of laser wavelengths. For a 1.3- μm system operating at 1.7 Gbit/s, the acceptable range is $\lambda_D \pm 5$ nm. The theory was compared with the experiments by measuring the bit-error rates for four lasers as a function of the bit rate. The Gaussian-spectrum assumption is found to underestimate the power penalty. We performed Monte Carlo simulations to study the overall system performance. Although we have considered only 1.3- μm systems, the analysis can be readily applied to the case of 1.55- μm systems making use of dispersion-shifted fibers and multimode semiconductor lasers.

ACKNOWLEDGMENT

The authors thank W. Reed and D. L. Philen for the measurement of fiber parameters and K. Ogawa for discussions.

REFERENCES

- [1] Y. Suematsu, "Long-wavelength optical fiber communication," *Proc. IEEE*, vol. 71, pp. 692–721, 1983.
- [2] T. Li, "Advances in optical fiber communications: An historical perspective," *IEEE J. Selected Areas Commun.*, vol. SAC-1, pp. 356–372, 1983.
- [3] K. Ogawa, "Analysis of mode-partition noise in laser systems," *IEEE J. Quantum Electron.*, vol. QE-18, pp. 849–855, 1982.
- [4] Y. Okano, K. Nakagawa, and T. Ito, "Laser-mode partition noise evaluation for optical fiber transmission," *IEEE Trans. Commun.*, vol. COM-28, pp. 238–243, 1980.
- [5] W. R. Throssell, "Partition noise statistics for multimode lasers," *J. Lightwave Technol.*, vol. LT-4, pp. 948–950, 1986.
- [6] K. Ogawa, in *Semiconductor and Semimetals*, vol. 22C, W. T. Tsang, Ed., Orlando, FL: Academic, 1985, pp. 299–330.
- [7] D. Marcuse, "Pulse distortion in single-mode fibers," *Appl. Opt.*, vol. 19, pp. 1653–1660, 1980.
- [8] S. D. Personick, "Receiver design for digital fiber-optic communication systems, Part I and II," *Bell Syst. Tech. J.*, vol. 52, pp. 843–886, 1973.
- [9] J. E. Midwinter, "A study of intersymbol interference and transmission medium instability for an optical fiber system," *Opt. Quantum Electron.*, vol. 9, pp. 299–304, 1977.
- [10] D. L. Philen, private communication.
- [11] T. M. Shen and P. J. Anthony, "A super-Lorentzian model for mode-partition noise in multifrequency lasers," to be published.




Govind P. Agrawal (M'83-SM'86) was born in Kashipur, India. He received the M.S. and Ph.D. degrees from the Indian Institute of Technology, New Delhi, in 1971 and 1974, respectively.

After spending several years at the Ecole Polytechnique, France, the City University of New York, and Quantel, France, he joined AT&T Bell Laboratories in 1982 as a Member of the Technical Staff. His research interests have been in the field of quantum electronics, nonlinear optics, and laser physics. He is an author or coauthor

of more than 100 research papers, several review articles and book chapters, and a book entitled *Long-Wavelength Semiconductor Lasers*.

Dr. Agrawal is a Fellow of the Optical Society of America and a member of the American Physical Society.

*




Philip J. Anthony (M'81) was born in New Bremen, OH, on May 6, 1952. He received the B.S. degree from the University of Dayton, OH, in 1974, and the M.S. and Ph.D. degrees from the University of Illinois, Urbana, in 1975 and 1978, respectively, all in physics.

Since 1978 he has been a Member of the Technical Staff at AT&T Bell Laboratories, Murray Hill, NJ, working on the growth and characterization of semiconductor lasers. In 1982 he assumed supervisory responsibility for InGaAsP

laser development. In 1987, he was appointed Head of the Optoelectronic Devices Department, with responsibilities for developing devices using integrated optics, such as optical switches.

Dr. Anthony is a member of Sigma Pi Sigma, Sigma Xi, and American Physical Society, and the American Association for the Advancement of Science.

*



Tek-Ming Shen (M'81) was born in Hong Kong on January 6, 1949. He received the B.Sc. degree with highest honors in physics and mathematics and the B.Sc. (special) honors degree in physics from the University of Hong Kong, in 1972 and 1973, respectively, and the Ph.D. degree in physics from the University of California, Berkeley, in 1979.

From 1979 to 1980 he was a Postdoctoral Research Physicist at the University of California, Berkeley. During his doctoral and postdoctoral

work, he researched superconductor-insulator-superconductor tunnel junctions as millimeter-wave mixers. In 1980 he joined the Technical Staff of AT&T Bell Laboratories, Murray Hill, NJ, where he has been involved in the characterization of dynamic properties, InGaAsP multifrequency and single-frequency semiconductor lasers, and their performance in lightwave communication systems.